



PT-KW SERIES

High Power Pulse Traveling WaveTube Amplifiers

3-8 Kilowatts Pulsed
1.0-18.0 GHz, up to 10% Duty Cycle

Features Include:

- Digital Display Monitors: Collector Current, Collector Voltage, Helix Current, Helix Voltage, Forward RF Power, Reflected RF Power, Filament Hours, Beam Hours,
- Status Indicators: Power On, Standby, RF On/Operate,
- Faults: Helix Overcurrent, VSWR Overload, Thermal Overloads, Air Flow, Collector Overcurrent
- Controls: Power On/Off, Standby, RF On/Operate, Fault Reset, Local/Remote
- Ease of Maintenance
- Designed to meet the safety requirements of the IEC-348 and Underwriters Laboratory of American Standards
- Broadband Coverage
- Applications Include: MIL-STD-461/462, RTCA/D0-160, SAE Specifications, Radiated Susceptibility, Bellcore testing, Broadband Communications.
- Ruggedized Versions are available for Shipboard and Airborne applications



RF Specifications

Model Number	Frequency Range (GHz)	Min Pwr Out* (kWatts)	Min Sat Gain* (dB)	Max NF (dB)
PT1412-5Kw	1.2-1.4	5.0	67	35
PT1412-6Kw	1.2-1.4	6.0	68	35
PT3525-5	2.5-3.5	5.0	67	35
PT4830-5	3.0-4.8	5.0	67	35
PT5727-4Kw	2.7-5.7	4.0	66	35
PT128-3	8.2-12.4	3.0**	65	35
PT108-6	8.7-10.5	6.0	68	35
PT1715-4	15-17	4.0**	66	35
PT9593-4Kw	9.3-9.5	4.5	66	35
PT128-8Kw	8-12	8.0	69	35
PT1093-5Kw	9.3-10	5.0	67	35

*Higher output power and gains available

**Over majority of Frequency Range

INSTRUMENTS FOR INDUSTRY INC.

903 South Second Street, Ronkonkoma, NY 11779

Tel: 631-467-8400 • Fax: 631-467-8558 • E mail: sales@ifi.com

www.ifi.com

PT-KW SERIES

High Power Traveling Wave Tube Amplifiers

3–8 Kilowatts Pulsed
1.0-18.0 GHz, up to 10% Duty Cycle

Prime Power:

100/115/220/230 or 240VAC $\pm 10\%$ 50/60 Hz, single phase
115/208 or 200/220/230/240VAC $\pm 10\%$ 50/60 Hz,
three phase Wye, Delta and/or 400 Hz power is available

Mechanical

Dimensions: 14"H x 19"W x 27"D
(Rack Mountable) (356mm x 483mm x 686mm)
Weight: 170 pounds typical (77kg)
Cooling: Internal forced air

Remote Operation

GPIO, RS422, RS485, RS232, or TTL Remote Control

Environmental

Operating Temperature: 0 - 50°C (40°C @ 10,000 Feet)
Relative Humidity: 95% (non-condensing)
Operating Altitude: 10,000 feet maximum
Non-operating Temp.: -20 to 70°C
Non-operating Altitude: 50,000 feet maximum


RF Specifications

Spurious Outputs: -40 dBc, maximum.
-50 dBc, available.
Input Impedance: 50 Ohms, VSWR 2.0:1
Output Impedance: 50 Ohms, VSWR 2.0:1
2.5:1 maximum.
Input Connector: Type N (Female).
Output Connector: 1.0 to 8.0 GHz,
Type SC (Female),
8.0 to 12.0 GHz, WR90
12.0 to 18.0 GHz, WR62
7.5 to 18.0 GHz, WRD750
6.0 to 18.0 GHz, WRD650
(Other waveguides available
Option 117)

To view typical performance data go to
www.ifi.com/typdata.htm

Outline Drawing:

Specifications subject to change without notice



INSTRUMENTS FOR INDUSTRY INC.

IFI 中国总代理: 北京康泰电子有限公司
Tel: 8610-58731155 • Email: sales@quatronix-cn.com
www.ifi.com (英文) www.quatronix-cn.com (中文)